

Amendments to the claims (this listing replaces all prior versions):

1. (currently amended) A system comprising:

in a vehicle suspension having an actuator, ~~a clamp circuit including~~ switch circuitry powered by energy from movement of the actuator to ~~generate a passively~~ damp ~~[[ing]]~~ characteristic of the actuator during a failure.
2. (previously presented) The system of claim 1 in which the actuator has a coil assembly, the switch circuitry including a switch for electrically connecting the coil assembly.
3. (original) The system of claim 2 in which the coil assembly is a multiple-phase coil assembly, the switch electrically connecting one or more coil ends to change the passive damping characteristic of the actuator.
4. (previously presented) The system of claim 2 in which the switch circuitry comprises a solid-state device.
5. (currently amended) The system of claim 4 ~~in which the~~ also comprising, in the vehicle suspension, clamp circuit including ~~[[es]]~~ a rectifier,

in which ~~and~~ the switch circuitry comprises a single unidirectional switch.
6. (previously presented) The system of claim 1 in which the actuator includes an armature and a stator, the movement of the actuator generating a back electromotive force (EMF) as a result of the armature moving relative to the stator within the actuator, the back EMF powering the switch circuitry.
7. (original) The system of claim 6 in which the back EMF is boosted by a supplemental circuit.

8. (original) The system of claim 7 in which the supplemental circuit comprises a bipolar Royer oscillator capable of operating at an input voltage of approximately 0.5 volts.
9. (currently amended) The system of claim 1 in which the ~~clamp circuit~~ switch circuitry is also enabled during vehicle startup and shutdown.
10. (cancelled)
11. (currently amended) The system of claim 1 in which the ~~clamp circuit~~ switch circuitry is pulsed to change the passive damping characteristic of the actuator.
12. (currently amended) A system comprising:

in a vehicle suspension system having an actuator, an active clamp function provided by power-switching devices for the actuator; and

~~a clamp circuit including~~ switch circuitry powered by energy from a motion of the actuator to generate a passive damping function during a failure.
13. (previously presented) The system of claim 12 in which the actuator has a multiple-phase coil assembly, the switch circuitry including a switch for electrically connecting one or more coil ends to change a passive damping characteristic of the actuator.
14. (previously presented) The system of claim 13 in which the switch circuitry comprises a solid-state device.
15. (currently amended) The system of claim 14 ~~in which the~~ also comprising a clamp circuit including [[es]] a rectifier,

in which and the switch circuitry comprises a single unidirectional switch.

16. (currently amended) The system of claim 12 in which the ~~clamp-circuit~~ switch circuitry is also enabled during a vehicle startup and shutdown.
17. (cancelled)
18. (currently amended) The system of claim 12 in which the ~~clamp-circuit~~ switch circuitry is pulsed to change the passive damping characteristic of the actuator.
19. (currently amended) A vehicle suspension system comprising:

an electronic controller adapted to produce an actuator control signal; and

an actuator adapted to receive electrical power from an external power source and to produce a controlled force in response to the actuator control signal produced by the electronic controller,

the actuator ~~comprising a clamp-circuit~~ including switch circuitry powered by energy from power generated within the actuator by movement of the actuator itself to generate a passive damping characteristic of the actuator during a failure.
20. (previously presented) The system of claim 19 in which the actuator has a coil assembly, the switch circuitry including a switch for electrically connecting the coil assembly.
21. (original) The system of claim 20 in which the coil assembly is a multiple-phase coil assembly, the switch electrically connecting one or more coil ends to change the passive damping characteristic of the actuator.
22. (original) The system of claim 20 in which a movement of the actuator generates an electromotive force (EMF) to operate the switch adapted to receive the electromotive force to maintain electrical connection between windings.

23. (previously presented) The system of claim 20 in which the switch circuitry comprises a solid-state device.
24. (currently amended) The system of claim 23 ~~in which the~~ also comprising a clamp circuit including [[cs]] a rectifier,

in which ~~and~~ the switch circuitry comprises a single unidirectional switch.
25. (currently amended) The system of claim 19 in which the ~~clamp circuit~~ switch circuitry is pulsed to change the passive damping characteristic of the actuator.
26. (currently amended) A method comprising:

in a vehicle suspension having an actuator, during a failure,

generating a passive damping characteristic of the actuator using ~~through a clamp circuit~~ ~~including~~ switch circuitry powered by energy from movement of the actuator.
27. (previously presented) The method of claim 26 in which the actuator has a coil assembly, the switch circuitry including a switch for electrically connecting the coil assembly.
28. (original) The method of claim 27 in which the coil assembly is a multiple-phase coil assembly, the switch electrically connecting one or more coil ends to change the passive damping characteristic of the actuator.
29. (previously presented) The method of claim 27 in which the switch circuitry comprises a solid-state device.
30. (currently amended) The method of claim 29 in which ~~the~~ a clamp circuit includes a rectifier and the switch circuitry comprises a single unidirectional switch.

31. (previously presented) The method of claim 26 in which the actuator includes an armature and a stator, the movement of the actuator generating a back electromotive force (EMF) as a result of the armature moving relative to the stator within the actuator, which powers the switch circuitry.
32. (original) The method of claim 31 in which the back EMF is boosted by a supplemental circuit.
33. (original) The method of claim 32 in which the supplemental circuit includes a bipolar Royer oscillator capable of operating at an input voltage approximately 0.5 volts.
34. (currently amended) The method of claim 26 in which the ~~elamp-circuit~~ switch circuitry is also enabled during a vehicle startup and shutdown.
35. (cancelled)
36. (original) The method of claim 26 in which the actuator is powered by a power electronics module that further provides an active clamp to the actuator.
37. (currently amended) The method of claim 36 in which the active clamp and the ~~elamp circuit~~ switch circuitry are simultaneously enabled when a failure is detected or during a vehicle shutdown.
38. (currently amended) The method of claim 36 in which the active clamp is enabled and the ~~elamp-circuit~~ switch circuitry is disabled sequentially during a vehicle startup.
39. (currently amended) The method of claim 36 in which the ~~elamp-circuit~~ switch circuitry and the active clamp are sequentially disabled when switching back from failure to normal operation mode.

40. (currently amended) The method of claim 36 in which a clamp circuit status signal is fed to the power electronics module to inhibit the power electronics module from switching when the ~~clamp circuit~~ switch circuitry is enabled.
41. (currently amended) The method of claim 26 in which the ~~clamp circuit~~ switch circuitry is pulsed to change the passive damping characteristic of the actuator.
- 42-43. (cancelled)
44. (previously presented) The system of claim 36 in which the power electronics module is powered by a battery.
45. (previously presented) The system of claim 36 in which the power electronics module is powered by a large valued capacitor.
- 46-58. (canceled).
59. (new) The system of claim 1 in which the failure includes a failure of a power supply of a vehicle including the system.
60. (new) The system of claim 1 in which the failure includes a failure of a connection between a power supply and the suspension.
61. (new) The system of claim 1 in which the switch circuitry is also powered by energy from movement of the actuator to generate the passive damping characteristic during startup and shutdown of a vehicle including the system.
62. (new) A method for use in a vehicle having a power generation system and a suspension having an actuator, the method comprising:

Applicant : Paul T. Bender
Serial No. : 10/657,496
Filed : September 8, 2003
Page : 8 of 11

Attorney's Docket No.: 02103-381001 / AABOSS16

even when the power generation system fails to provide power, using power derived from movement of the actuator to electrically enable a switch to passively damp the actuator.